

## Specifications. The new BMW 5 Series Sedan. 523i, 528i. (Not for US Market)

		BMW 523i	BMW 528i
Body			
No of doors/seats		4/5	4/5
Length/width/height (unladen)	mm	4899 / 1860 / 1464	4899 / 1860 / 1464
Wheelbase	mm	2968	2968
Track, front/rear	mm	1600 / 1627	1600 / 1627
Ground clearance	mm	141	141
Turning circle	m	11.95	11.95
Tank capacity	app ltr	70	70
Cooling system incl heater	ltr	9.0	9.0
Engine oil <sup>1)</sup>	ltr	6.5	6.5
Weight, unladen, to DIN/EU	kg	1625 / 1700 (1650 / 1725)	1635 / 1710 (1655 / 1730)
Max load to DIN	kg	610	610
Max permissible	kg	2235 (2260)	2245 (2265)
Max axle load, front/rear	kg	1070 / 1265 (1070 /1270)	1070 / 1265 (1070 / 1270)
Max trailer load (12%), braked/unbraked	kg	1900 / 750 (2000 / 750)	2000 / 750
Max roofload/max towbar dwnl	kg	100/90	100/90
Luggage comp capacity	ltr	520	520
Air resistance	Cd x A	0.28 x 2.35	0.28 x 2.35
Power Unit			
Config/No of cyls/valves		Straight-six / 4	Straight-six / 4
Engine technology		Direct fuel injection (High Precision Injection),	Direct fuel injection (High Precision Injection),
		lean-burn	lean-burn
Capacity, effective	СС	2996	2996
Stroke / bore	mm	88.0 / 85.0	88.0 / 85.0
Compression ratio	:1	12.0	12.0
Fuel grade		min RON 91	min RON 91
Max output	kW/hp	150 / 204	190 / 258
at	rpm	6100	6600
Max torque	Nm/lb-ft	270/199 1500-4250	310/228 2600-5000
At	rpm	1300-4230	2000-3000
Electrical System		00 (00) (1	20.500.11
Battery/installation	Ah/-	80 (90) / luggage comp	80 (90) / luggage comp
Alternator	A/W	210 / 2940	210 / 2940
<b>Driving Dynamics and Safety</b>			
Suspension, front	Double track control arm axle with separate lower track arm level, aluminium, small steering roll radius, anti-dive		
Suspension, rear	Integral-V multi-arm axle, aluminium, with steering function, anti-squat and anti-dive, double acoustic separation		
Brakes, front			n swing-calliper disc brakes in frame structure
Diameter	mm	330 x 24 / inner-vented	348 x 30 / inner-vented
Brakes, rear		Single-piston	aluminium swing-calliper disc brakes
Diameter	mm	330 x 20 / inner-vented	330 x 20 / inner-vented
Driving stability systems	Standard: DSC incl ABS and DTC Dynamic Traction Control, CBC Cornering Brake Control, DBC Dynamic Brake Control, Dry Braking function, Fading Compensation, Start-Off Assistant; optional: Adaptive Drive		
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel belts on all seats with belt stopper, belt tightener and belt force limiter at the front, crash-activated headrests at the front, crash sensors,  Tyre Defect Indicator	
Steering			er Steering (EPS) with Servotronic; nal: Integral Active Steering
Steering transmission, overall	:1	17.1	17.1
Tyres, front/rear		225/55 R17 97W	225/55 R17 97W
Rims, front/rear		8J x 17 light-alloy	8J x 17 light-alloy

## Specifications. The new BMW 5 Series Sedan.

523i, 528i.

			BMW 523i	BMW 528i			
BMW Connected	Drive						
Comfort	<u> </u>	Optional: BMW Assist including Enquiry Service, remote-control functions and V-Info+, BMW TeleServices, integration of mobile terminals					
Infotainment		Optional: access to the internet, BMW Online including Parkinfo, National Info, Google Directory Service, News, Weather Realtime and BMW Routes					
Safety		Optional: Adaptive Headlights with Bending Lights, variable light distribution and adaptive headlight range control, High-Beam Assistant, Park Distance Control, back-up camera, Surround View including Side View and Top View, BMW Night Vision with detection of persons, Head-Up Display, Parking Assistant, collision warning with brake activation function in combination with Active Cruise Control with Stop & Go, Lane Change Warning, Lane Departure Warning, Speed Limit Info, Speed Limit Device, Automatic/Enhanced Emergency Call					
Transmission							
Type of gearbox		Six-speed manual (optional: eight-speed automatic with Steptronic)		• • •			
Gear ratios I	:1	4.323 (4.714)	3.498 (4.714)				
	II	:1	2.456 (3.143)	1.984 (3.143)			
	III	:1	1.659 (2.106)	1.313 (2.106)			
	IV	:1	1.230 (1.667)	1.000 (1.667)			
	V	:1	1.000 (1.285)	0.809 (1.285)			
	VI	:1	0.848 (1.000)	0.701 (1.000)			
	VII	:1	- (0.839)	- (0.839)			
	VIII	:1	- (0.667)	- (0.667)			
	R	:1	3.938 (3.295)	3.300 (3.295)			
Final drive		:1	3.231 (3.385)	4.100 (3.385)			
Performance							
Power-to-weight	ratio	kg/kW	10.8 (11.0)	8.6 (8.7)			
Output per litre		kW/hp	50.1/68.1	63.4/86.2			
Acceleration 0	-100 km/h	sec	7.9 (8.2)	6.6 (6.7)			
Standi	ng-start km	sec	28.5 (29.0)	26.5 (26.6)			
In 4th gear 80	-120 km/h	sec	9.0 (-)	7.0 (-)			
Top speed		km/h	238 (234)	250			
BMW EfficientDy							
BMW EfficientDyn standard features	,		Brake Energy Regeneration with recuperation of nanual gearbox models), intelligent lightweight of ancillary units, air flap control, Electric Pow compressor, tyres with reduc	construction, on-demand operation ver Steering (EPS), detachable a/c			
Fuel Consump in	EU Cycle						
Urban		ltr/100	10.5 (10.5)	10.4 (10.4)			
Extra-urban		ltr/100	5.9 (5.9)	6.3 (6.0)			
Combined		ltr/100	7.6 (7.6)	7.8 (7.6)			
CO <sub>2</sub>		g/km	177 (178)	182 (178)			
		0,					

 $Specifications\ applicable\ to\ ACEA\ markets,\ data\ relevant\ to\ homologation\ applicable\ in\ part\ only\ to\ Germany\ (weight)\ Figures\ in\ brackets\ apply\ to\ automatic\ transmission\ models$ 

<sup>1)</sup> Oil change